


FireLock® Sprinklers – Standard Commercial

Standard Commercial


Note: Sprinkler approvals and listings can vary by model, temperature and finish. For complete regulatory information, consult the product submittal publication.

Model No./SIN	K-Factor Imp. S.I. §	Deflector Type	Response	Nom. Thread Size In. (NPT) mm	Temperature Rating								Coatings and Finishes						Approvals and Listings †						Sub. Pub.	
					135° F/57° C	155° F/68° C	162° F/72° C	165° F/74° C	175° F/79° C	200° F/93° C	212° F/100° C	286° F/141° C	360° F/182° C	OPEN	Plain Brass	Chrome	White or Cream	Wax	Nickel/Teflon	Flat Black	Custom	Bright White	cULus	UL		ULC


LIGHT HAZARD, ORDINARY HAZARD, STORAGE *

K5.6 	Model	K-Factor	Deflector Type	Response	Nom. Thread Size	135° F/57° C	155° F/68° C	162° F/72° C	165° F/74° C	175° F/79° C	200° F/93° C	212° F/100° C	286° F/141° C	360° F/182° C	OPEN	Plain Brass	Chrome	White or Cream	Wax	Nickel/Teflon	Flat Black	Custom	Bright White	cULus	UL	ULC	FM	VdS	LPCB	CNBOP	CCC	VNI/PO	40.10			
	V2703	5.6	Upright	Standard	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2707	8.1	Pendent	Standard	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2707	5.6	Recessed Pendent	Standard	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2704	8.1	Upright	Quick	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2708	8.1	Pendent	Quick	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2708	5.6	Recessed Pendent	Quick	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•


LIGHT HAZARD, ORDINARY HAZARD, STORAGE *

K5.6 	Model	K-Factor	Deflector Type	Response	Nom. Thread Size	135° F/57° C	155° F/68° C	162° F/72° C	165° F/74° C	175° F/79° C	200° F/93° C	212° F/100° C	286° F/141° C	360° F/182° C	OPEN	Plain Brass	Chrome	White or Cream	Wax	Nickel/Teflon	Flat Black	Custom	Bright White	cULus	UL	ULC	FM	VdS	LPCB	CNBOP	CCC	VNI/PO	40.11			
	V2709	5.6	Horizontal Sidewall	Standard	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2709	8.1	Recessed Horiz. Sidewall	Standard	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V2710	8.1	Horizontal Sidewall	Quick	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
V2710	5.6	Recessed Horiz. Sidewall	Quick	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

LIGHT HAZARD, ORDINARY HAZARD

K8.0 	Model	K-Factor	Deflector Type	Response	Nom. Thread Size	135° F/57° C	155° F/68° C	162° F/72° C	165° F/74° C	175° F/79° C	200° F/93° C	212° F/100° C	286° F/141° C	360° F/182° C	OPEN	Plain Brass	Chrome	White or Cream	Wax	Nickel/Teflon	Flat Black	Custom	Bright White	cULus	UL	ULC	FM	VdS	LPCB	CNBOP	CCC	VNI/PO	40.15 40.16 40.16			
	V3401	8.0	Upright	Standard	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V3405	8.0	Pendent	Standard	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V3405	11.5	Recessed Pendent	Standard	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V3402	8.0	Upright	Quick	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V3406	8.0	Recessed Pendent	Quick	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V3409	8.0	Horizontal Sidewall	Standard	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
	V3409	11.5	Recessed Horiz. Sidewall	Standard	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
V3410	8.0	Horizontal Sidewall	Quick	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
V3410	11.5	Recessed Horiz. Sidewall	Quick	3/4 20	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

CONVENTIONAL (OLD STYLE)

K5.6 	Model	K-Factor	Deflector Type	Response	Nom. Thread Size	135° F/57° C	155° F/68° C	162° F/72° C	165° F/74° C	175° F/79° C	200° F/93° C	212° F/100° C	286° F/141° C	360° F/182° C	OPEN	Plain Brass	Chrome	White or Cream	Wax	Nickel/Teflon	Flat Black	Custom	Bright White	cULus	UL	ULC	FM	VdS	LPCB	CNBOP	CCC	VNI/PO	40.17		
	V2725	5.6	Pendent/Upright	Standard	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•
V2726	8.1	Pendent/Upright	Quick	1/2 15	•	•				•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

* UL Listed to 250psi, FM Approved to 175 psi.

§ For K-Factor when pressure is measured in Bar, multiply S.I. units by 10.0.

† Not all combinations of temperature ratings and wax finishes are Approved or Listed. Check specific submittals for combinations. V27 and V34 models are MEA (#62-99-E) and CSFM (#7690-0531.112) Approved.

Approved for use on sloped ceilings.

** Recessed pendent up to 1/2"/13 mm adjustment; For rooms 12 x 12 ft. to 20 x 20 ft./3.7 x 3.7 m to 6.1 x 6.1 m.

*** Recessed pendent up to 1/4"/6 mm adjustment; For rooms 12 x 12 ft. to 18 x 18 ft./3.7 x 3.7 m to 5.5 x 5.5 m.

‡‡ Also available with Sealing Gasket for Clean Room Applications. Request publication 40.53.

All Victaulic sprinklers are available in British Standard Pipe Threads. Contact Victaulic for details.

FireLock® Automatic Sprinklers

Wrenches



Wrench Type	Wrench Model													
	Model V25	Model V26 Foam Nozzle	Model V27	Model V27-2	Model V29 Flush	Model V29-1	Model V33	Model V34	Model V36	Model V38-4	Model V38-5 Cabinet Socket	Model V39	Model V44	Model V46
OPEN END	●	●	●					●	●				●	●
RECESSED				●				●	●					
SOCKET					●	●	●			●	●			
FLUSH					●	●								
CONCEALED				●			●		●	●	●	●		

For Complete Information
Request Publication **40.80**

Accessories



SPRINKLER GUARDS

For Complete Information
Request Publication **40.83**



EXPANSION PLATE

For Complete Information
Request Publication **40.84**



ESCUTCHEONS

For Complete Information Request
Publication **40.88**



SPRINKLER STORAGE CABINET

For Complete Information
Request Publication **40.81**